

SIEMENS



iQ 700

**Glass hood
LC955HA60B stainless steel**

Design

- 900 mm wide
- Soft touch button control
- White electronic display
- Stainless steel hood with glass canopy
- Height adjustable chimney sections
- For wall mounted installation

Key features

- Electronic control
- Electronic power level display
- Grease and charcoal filter saturation indicators
- Automatic after running (10mins)
- 2 x 20W 20W halogen lights
- softLight with dimmer function
- 1 x metal grease filter cassette
- Removable multi-zone extraction filter box


Performance/technical information

- Suitable for ducted and re-circulating operation
- Maximum extraction rate 470 m³/h
- Noise level at maximum normal setting: 48 dB (A); equivalent to 62 dB (A) re 1pW according to EN 60704-2-13
- 3 x power levels plus intensive setting
- Automatic intensive revert

Optional accessory

- Re-circulating kit - LZ51850


Included accessories



Optional accessories

- LZ51850 Recirculating kit

Alternative colors available



Technical Data

Characteristics

Color chimney : Stainless steel
 Typology : Chimney
 Approval certificates : CE, VDE
 Length electrical supply cord (m) : 130.0
 Height of the chimney (mm) : 630-1025/665-1095
 Height of product, without chimney (mm) : 75
 Dimensions of the product, with chimney (if exists) (mm) : 740-1170 x 900 x 500
 Net weight (kg) : 22.00
 Type of control : electronical
 Number of speed settings : 3-stage + intensive
 Maximum output air extraction (m3/h) : 470
 Boost position output recirculating (m3/h) : 350
 Maximum output recirculating air (m3/h) : 310
 Boost position air extraction (m3/h) : 590
 Number of lights (Stck) : 2
 Diameter of air outlet (mm) : 150 / 120
 Grease filter material : Metal grease filter

Consumption and connection features

Connection Rating (W) : 240
 Voltage (V) : 220-230
 Frequency (Hz) : 50
 Plug type : GB plug
 Installation typology : Wall-mounted

Siemens
LC955HA60B
Chimney hood

Predecessor:

Successor:

EAN code:
4242003434284

sales programme:

